

Data Sheet
LUMOTAST 22 Emergency Stop Pushbutton
1.15.105.0xx/xxxx



General Data

Type designation:	LUMOTAST 22
Description:	Emergency Stop Pushbutton i.a.w. EN 13850
Approbations:	-
Switch type:	2NC, 1NO / 2NC / 2NC + LED
Protection class:	IP65
Storage temperature (max.):	-40 °C ... 80 °C
Operating temperature (max.):	-25 °C ... 70 °C
Mech. useful life / B10:	15,000

Data Sheet
LUMOTAST 22 Emergency Stop Pushbutton
1.15.105.0xx/xxxx

Electrical Data according to IEC/EN 60947-5-1 (VDE 0660, Part 200)

	Alternating current	Direct current
Use category:	AC15	DC 13
Rating insulation voltage Ui:	250 V	250 V
Rating operation voltage Ue:	250 V	240 V
Therm. Steady current:	2.5 A	2.5 A

Technical Data

Mounting hole:	22.3 mm
Torque (assembly nut):	max. 1.9 Nm
Release:	Rotating release (left/right)
Mounting position:	any position
Norms:	EN 60947-5-1, EN 60947-5, EN 60068, EN 13850

Note

with integrated transmitter (2NC, 2NC + 1NO, 2NC illuminable with white LED)

- Toggle position display
- i.a.w. EN 13850

Item numbers

LUMOTAST 22 Emergency Stop Pushbutton with 2NC	1.15.105.001/0000
LUMOTAST 22 Emergency Stop Pushbutton with 2NC, illuminable	1.15.105.011/0000
LUMOTAST 22 Emergency Stop Pushbutton with 2NC + 1NO	1.15.105.021/0000

Preliminary technical data; revisions reserved

3D data (in ".step" or ".igs" format upon request).